ATTORNEY DOCKET NO.; 47234-0005-00-US

U.S. Application No. 10/530,679

Response to Office Action mailed: January 27, 2009 Response dated: April 22, 2009

Page 2

AMENDMENTS TO THE CLAIMS

The following listing of the claims will replace all prior versions, and listings, of claims in the application.

LISTING OF THE CLAIMS:

Please amend the claims as follows:

- Claim 1. (Currently Amended): A method of manufacturing a plant finished product, comprising the step of processing a plant or a processed material thereof with a high-temperature and high-pressure liquid, gas, or fluid having a temperature of 140 to 500°C and a pressure of 0.1 to 100 MPa, under conditions where an oxygen concentration is 0 to 1 µg/mL.
- Claim 2. (Currently Amended): The method of manufacturing a plant finished product according to claim 1, wherein the plant or the processed material thereof is processed for 1 to 3,600 seconds with liquid, gas, or fluid having a temperature of 140 to 500°C and a pressure of 0.1 to 100 MPa, under conditions where an oxygen concentration is 0 to 1 ug/mL.
- Claim 3. (Currently Amended): The method of manufacturing a plant finished product according to claim 1, wherein the plant or the processed material thereof is processed for 10 to 1,200 seconds with liquid; a gas, or fluid having a temperature of 160 to 250°C and a pressure of 0.5 to 4.5 MPa, under conditions where an oxygen concentration is 0 to 1 µg/mL.
- Claim 4. (Currently Amended): The method of manufacturing a plant finished product according to claim 1, wherein the liquid, gas, or fluid is derived from a deaerated liquid.
- Claim 5. (Currently Amended): The method of manufacturing a plant finished product according to claim 1, wherein a gas having an oxygen concentration of 0 to 1 µg/mL is used to purge a processing container before processing.

ATTORNEY DOCKET NO.: 47234-0005-00-US

U.S. Application No. 10/530,679

Response to Office Action mailed: January 27, 2009

Response dated: April 22, 2009

Page 3

Claim 6. (Original): The method of manufacturing a plant finished product according to

claim 5, wherein the gas having an oxygen concentration of 0 to 1 $\mu\text{g/mL}$ is an inert gas, carbon

dioxide, or deoxidized gas.

Claim 7. (Previously Presented): The method of manufacturing a plant finished product

according to claim 1, wherein the plant or the processed material thereof is a plant containing

lignin or a processed material thereof.

Claim 8. (Original): The method of manufacturing a plant finished product according to

claim 7, wherein the lignin-containing plant or the processed material thereof is at least one

selected from grains, trees, teas, processed materials thereof, and a by-product of mashing.

Claims 9-20. (Canceled).

Claim 21. (Currently Amended): A method of manufacturing a composition containing

vanillin, comprising the step of processing a plant containing lignin or a processed material

thereof with a high-temperature and high-pressure liquid, gas, or fluid having a temperature of 140 to 500°C and a pressure of 0.1 to 100 MPa to increase the amount of vanillin contained

therein.

Claim 22. (Canceled).

Claim 23. (Previously Presented): The method of manufacturing a composition

containing vanillin according to claim 21, wherein the high-temperature and high-pressure

processing is carried out for 1 to 3,600 seconds.

Claim 24. (Previously Presented): The method of manufacturing a composition

containing vanillin according to claim 21, wherein the composition containing vanillin is a raw

material of food and drink.

DC01/2190618.1

ATTORNEY DOCKET NO.: 47234-0005-00-US

U.S. Application No. 10/530,679

Response to Office Action mailed: January 27, 2009 Response dated: April 22, 2009

Response d Page 4

Claim 25. (Previously Presented): The method of manufacturing a composition

containing vanillin according to claim 21, wherein the composition containing vanillin is a raw

material of liquors or tea drinks.

Claim 26. (Previously Presented): The method of manufacturing a composition

containing vanillin according to claim 21, wherein the plant containing lignin or the processed

material thereof is derived from grain.

Claim 27. (Original): The method of manufacturing a composition containing vanillin

according to claim 26, wherein the grain is malt.

Claim 28. (Previously Presented): The method of manufacturing a composition

containing vanillin according to claim 21, wherein the vanillin content of the composition containing vanillin is three times or more compared to that of the plant containing lignin or the

processed material thereof before high-temperature and high-pressure processing.

Claim 29. (Previously Presented): The method of manufacturing a composition containing

vanillin according to claim 21, comprising a step of exposing a product obtained through high-

temperature and high-pressure processing to a low pressure from a high pressure to transpire

moisture and puff out the product.

Claim 30. (Previously Presented): The method of manufacturing a composition

containing vanillin according to claim 21, wherein an extruder is used.

Claim 31. (Previously Presented): The method of manufacturing a composition

containing vanillin according to claim 29, wherein the composition containing vanillin is puffed

out into a stick-like shape, a cylindrical column shape, a polygonal prism shape, a spherical

shape, or a polyhedron shape.

DC01/2190618.1

ATTORNEY DOCKET NO .: 47234-0005-00-US

U.S. Application No. 10/530,679

Response to Office Action mailed: January 27, 2009

Response dated: April 22, 2009

Page 5

Claim 32. (Previously Presented): The method of manufacturing a composition containing vanillin according to claim 21, wherein the plant, the processed material thereof, or

the raw material containing the plant and/or the processed material thereof is processed under

conditions where an oxygen concentration is 0 to 1 $\mu g/mL$.

Claims 33-38. (Canceled).

Claim 39. (Currently Amended): A method of manufacturing a plant finished product,

comprising the step of processing malt with a high-temperature and high-pressure water vapor gas having a temperature of 140 to 500°C and a pressure of 0.1 to 100 MPa, under conditions

where an oxygen concentration is 0 to 1 µg/mL.

Claim 40. (New): The method of manufacturing a plant finished product according to

claim 1, wherein the plant or the processed material thereof is processed with the gas having a

temperature of 160 to 250°C and a pressure of 0.25 to 4.5 MPa